

Applications

- Drive simulations with standard Electric Vehicle tests: FUDS, SFUDS, GSFUDS, DST and ECE-15L
- Battery Module Testing
- Start/Stop Testing
- Traction Battery Testing
- Supercapacitor / Ultracapacitor Testing
- Drive Cycle Testing

Features & Benefits

Bitrode's model FTV is a life cycle test system designed to perform standard electric vehicle, standby battery and supercapacitor tests. Designed for fast switching capability and high speed data acquisitions, the FTV is the ideal solution for demanding electric vehicle drive simulations.

Additional features include:

- Constant current, power or voltage control
- Discharge power recycled to AC line for cooler, more energy-efficient operation
- Bipolar capacity for discharging to below zero volts
- Drive Cycle Conversion utility automates test program development from acquired battery usage data
- Assignable data channels
- Drive Cycle Conversion utility automates test program development from acquired battery usage data
- Parallel circuit operation for greater flexibility in test specification
- Program execution is independent from the PC with VisualCN software
- Remote Binary Protocol via Ethernet connection available for 3rd party software control



General Specifications

Voltage:	0-100V*
Current:	Up to 1000A (2000A in parallel) up to 4000A with external PCC
Power:	up to 72kW (200kW in parallel) up to 288kW with external PCC
Accuracy:	±0.1% of FS**
Circuits:	up to 4
Data Sampling Rate:	up to 10mS

* Higher voltages available upon request. Contact your representative.

**Accuracy values are conservative assuming operation will be through the standard temperature range of 0-40° C and RH from 10-90% (non-condensing). Units calibrated and maintained in a temperature and humidity controlled environment can expect an accuracy of 0.02-0.05%FS.



Laboratory



System Options

- Up to three current ranges per circuit
- Temperature, pressure, flow rate, and cell voltage monitoring
- Digital inputs and Digital outputs with function assigned per individual program
- Expression-based program limit conditions
- Internal resistance calculation
- Integration with Battery Management Systems: CAN
- Ramp charge/discharge
- Constant resistance discharge
- Remote Input Output (RIO) box reduces excessive cable lengths when connecting to remote test stations
- Parallel controller (PCC) can control up to four circuits from separate units for higher power or higher current programs
- Module-front LCD display
- Custom-designed test leads
- Drive Cycle Conversion utility automates test program development from acquired battery usage data

Photos



BITRODE EUROPE
Via Spagna, 13
37069 Villafranca di Verona - Italy
tel: +39 (045) 6335797
fax: +39 (045) 6303911
email: sales-italy@bitrode.com

BITRODE HEADQUARTERS
9787 Green Park Industrial Drive
St. Louis, Missouri 63123 - USA
tel: +1 636 343-6112
fax: +1 636 343-7473
email: info@bitrode.com
www.bitrode.com

BITRODE ASIA
Room 4-1601, Xijing Park, Longyan Rd
300134 Beichen District
Tianjin, Republic of China
tel: (+86) 22 27270025
fax: (+86) 22 27270915
email: sales-china@bitrode.com